

BUBBLERS



K-Rain's pressure compensating bubblers ensure consistent flow rates over lower pressure ranges, ideal for watering trees and large shrubs.

Specifications

- Flow Rate:
 - TB-025: 0.25 GPM (0,057 m³/h; 0,95 l/m)
 - TB-05: 0.5 GPM (0,114 m³/h; 1,9 l/m)
 - TB-10: 1.0 GPM (0,227 m³/h; 3,8 l/m)
 - TB-20: 2.0 GPM (0,454 m³/h; 7,6 l/m)
 - TB-ADJ: 1.36 – 5.9 GPM (0,31 – 1,34 m³/h; 5 – 22 l/m)
- Operating Pressure: 20 – 50 PSI (1,4 – 2,8 bar)
- Spacing: 1' – 3' (0,3 m – 0,9 m)
- Inlet: 1/2" (1,3 cm) Female Thread
- Umbrella Pattern

SHRUB ADAPTERS

K-Rain Shrub Adapters are available for both male and female threaded nozzles. They are manufactured with high quality, UV inhibitor-infused ABS plastic for long life.

Specifications

- Adapts K-Rain nozzles for use with 1/2" threaded risers.
- Accepts protective, non-clogging K-Rain filters (shipped with nozzle)
- Durable, non-corrosive plastic construction



K-Rain Manufacturing Corp.
1640 Australian Avenue
Riviera Beach, FL 33404 USA
561.844.1002
FAX: 561.842.9493
1.800.735.7246 | www.krain.com

Models

TB-025	0.25 GPM (0, 95 LPM) Bubbler
TB-05	0.5 GPM (1,9 LPM) Bubbler
TB-10	1.0 GPM (3,8 LPM) Bubbler
TB-20	2.0 GPM (7,6 LPM) Bubbler
TB-ADJ	Adjustable Bubbler



Models

PSA	ShrubAdapter, Female Thread (for male nozzles)
PFSA	Shrub Adapter, Male Thread (for female nozzles)

Female Shrub Adapter



Male Shrub Adapter

