



The Pro-LC is an affordable, conventional controller with mar of the features of the reliable an robust Pro Ex 2.0 controller

Available in fixed 4, 8 or 12 stations, and as indoor or outdoor models, these compact controllers offer an array of user-friendly features including easy to follow programming; a full program screen display listing watering days, number of start times, number of stations and special programming; large LCD display; rain/freeze sensor compatibility; seasonal adjust for water conservation; a buried valve locator for easy maintenance and more.





K-Rain Manufacturing Corp. 1640 Australian Avenue Riviera Beach, FL 33404 USA 561.844.1002 FAX: 561.842.9493

1.800.735.7246 | www.krain.com



Features and Benefits

- Easy to follow programming
- Large LCD display
- Patented full program display feature shows watering days, number of start times, number of stations and special programming
- Rain sensor and rain/freeze sensor ready Allows automated operation to be controlled by sensor station by station.
- Seasonal adjust
- Buried valve locator
- Built-in Level Makes leveling the unit easy.

Models

OUTDOOR MODELS

3104 4 station, 110V AC internal transformer

3104-P 4 station, 110V AC internal transformer with pigtail

3104-220 4 station, 220V AC internal transformer 3108 8 station, 110V AC internal transformer

3108-P 8 station, 110V AC internal transformer with pigtail

3108-220 8 station, 220V AC internal transformer 3112 12 station, 110V AC internal transformer

3112-P 12 station, 110V AC internal transformer with pigtail

3112-220 12 station, 220V AC internal transformer

INDOOR MODELS

3104ID 4 station, 110V AC plug pack transformer
3104ID-220 4 station, 220V AC plug pack transformer
3108ID 8 station, 110V AC plug pack transformer
3108ID-220 8 station, 220V AC plug pack transformer
3112ID 12 station, 110V AC plug pack transformer
3112ID-220 12 station, 220V AC plug pack transformer

Specifications

OPERATING SPECIFICATIONS

- Station Run Times:1 minute to 6 hours
- Number of Programs: 3
- Number of Automatic Start Times:4 per program
- Program Watering Schedules:
 Odd (odd calendar days),
 Even (even calendar days),
 Custom (day of the week)

ELECTRICAL SPECIFICATIONS

- Power Input: 110V AC, 50/60Hz 240V AC, 50/60Hz
- Power Output: 24V AC 1.0Amp
- Power Backup: Lithium coin-cell battery maintains time and date during primary power outages.

DIMENSIONS

Height: 7" (17,8 cm)Width: 7" (17,8 cm)

Depth: 3.5" (8,9 cm)

